

XLS 10" Automotive



Type Number: 830514

Features:

This new series of state-of-the-art subwoofers continue to enhance Peerless' reputation for delivering the highest quality components for bass in the world. Called the XLS - for "Extra Long Stroke" - these new audio transducers add even more excursion, and completely eliminate distortion.

Driver Highlights: Thick Nomex cone, 51 mm voice coil, ALP



Specs:

Electrical Data

Nominal impedance	Zn	4	ohm
Minimum impedance	Zmin	2.4	ohm
Maximum impedance	Zo	28.5	ohm
DC resistance	Re	1.8	ohm
Voice coil inductance	Le	1.5	mH
Capacitor in series with x ohm	Cc	32	uF

T-S Parameters

Resonance Frequency	fs	39.4	Hz
Mechanical Q factor	Qms	6.37	
Electrical Q factor	Qes	0.42	
Total Q factor	Qts	0.39	
Ratio fs/Qts	F	--	
Force factor	Bl	11	Tm
Mechanical resistance	Rms	4.55	Kg/s
Moving mass	Mms	117	g
Suspension compliance	Cms	0.14	mm/N
Effective cone diameter	D	20.6	cm
Effective piston area	Sd	333	cm ²
Equivalent volume	Vas	21.4	ltrs
Sensitivity		92.2	dB
Ratio BL/√(Re)		96	


Power handling

100h RMS noise test (IEC)	--	W
Long-term Max System Power (IEC)	--	W
Max linear SPL (rms) @ power	--	dB/W
Short Term Max power	--	W

Voice Coil and Magnet Parameters

Voice coil diameter	51	mm
Voice coil height	33	mm
Voice coil layers	4	
Height of the gap	8	mm
Linear excursion +/-	--	mm
Max mech. excursion +/-	--	mm
Flux density of gap	1.04	mWb
Total useful flux	2.5	mWb
Diameter of magnet	147	mm
Height of magnet	35	mm
Weight of magnet	2.42	Kg

Frequency:



Mechanical Dimensions:

