

Index

Note: Page numbers followed by *f* indicate figures, *t* indicate tables, and *s* indicate schemes.

A

Acid gases, 428
Activated carbon
 characterization and status, 187
 markets and perspectives, 187
 principle, 186
Adiabatic compression. *See* Isentropic compression
Alcoholic fermentation, 56
Algebraic modeling languages (AML), 355
Alkaline water electrolysis, 311
Anaerobic digestion, 55
Analytic hierarchy process (AHP), 364
Analytic network process (ANP), 364
AUGMECON method, 363
Automotive fuels, 500–501, 503, 505

B

Battery electric cars, 168
Battery electric vehicles (BEV), 13–14
Binary integer programming problem, 354
Biogas/landfill gas
 characteristics, 112–113, 113*t*
 green hydrogen, 112
 reforming processes, 112–113
 via syngas route, 112, 112*s*
Biological methanation, 10–11, 315–316
Biomass, 44–45
Biomass gasification, 55–56, 55*f*
Bi-reforming, 147
Boil-off losses, 173–174
Boudouard reaction, 158–159
Buffer volumes
 HP buffers, 228–229
 with staged pressure, 233, 233*t*

C

California Fuel Cell Partnership (CaFCP), 25
Capital expenditure (CAPEX), 53
Captive fleet approach, 30, 30*f*
Carbon-based energy sources, 5

Carbon capture and storage (CCS)
 oxygen combustion, 57
 postcombustion capture processes, 57
 precombustion capture processes, 56
Carbon fiber reinforced polymer (CFRP-tanks), 170
Carbon footprint, 111
Carbon free energy vector, 521
Catalytic methanation, 313–314
Catalytic reforming unit (CRU), 449–451
CCS. *See* Carbon capture and storage (CCS)
CHA. *See* Concept hazard analysis (CHA)
Clean energy solutions, 5
Coal gasification, 54, 54*f*, 85
Coelectrolysis process, 316–317
CO₂ emissions, 4–5, 4*f*
Compressed gaseous hydrogen (CH), 503–505
Compression efficiency
 diaphragm compressor, 214, 216, 216*f*
 effect of capacity, 214, 216, 216*f*
 electric power, 215
 hydraulic boosters, 215
 isentropic/adiabatic efficiency, 214–215
 pneumatic boosters, 215
Concept hazard analysis (CHA)
 hazard identification method, 533, 535*t*
Continuous catalytic reforming (CCR) process, 444
Cosmogram, 301
Cryo-compressed hydrogen
 characterization, 176
 markets and perspectives, 176–177
Cryogenic phase separation method, 428

D

Decarbonization
 hydrogen
 as buffer, system resilience, 7
 energy distribution across sectors and regions, 7
 as feedstock using captured carbon, 7

Decarbonization (*Continued*)

- of industry energy use, 7
- large-scale, efficient renewable energy integration, 6

Decision making trial and evaluation laboratory (DEMATEL) method, 376–378

DES. *See* Discrete event simulation (DES)

Deterministic optimization approaches

- bi-criterion MILP problem, 373
- MILP problem, 373–374
- MINLP formulation, 374–375
- multiperiod spatially-explicit MILP formulation, 374
- network design problem, 373
- production-distribution network, 374
- SHIPMod model, 374

Diaphragm compressor, 214, 216, 216*f*

Direct computer mapping (DCM)

- programmable structures, 466
- usual network/net-based formalization, 466

Disability adjusted life years (DALYs), 70

Discrete event simulation (DES)

- model logic, 540–543, 541*f*
- SimEvents commercial software package, 543

DMR. *See* Dual methane reforming (DMR)

Domestic chain, 503–505

Dry reforming of methane (DRM), 113

catalysts

- endothermic reaction, 134–135
- metal catalysts, 134–135
- promoters, 137–139, 140–142*t*
- supports, 135–137

kinetic models

- bi-reforming, 147
- ER model, 139, 144–147, 145–146*t*
- LHHW model, 139, 144–147, 145–146*t*
- oxidative DRM, 147
- power law model, 139–144, 143*t*, 147
- Pt- and Ru-doped TiO₂ catalysts, 144
- thermodynamic equilibrium
- reaction pressure, 134, 134*f*

Dual methane reforming (DMR), 118–119, 119–120*f*

Dynamic programming (DP), 356–357

Dynamic risk analysis

- DES model logic, 540–543, 541*f*
- QRA, 539
- time dependence of events, 540, 540*f*
- time-dependent input parameters, 539
- time-dependent variables, 540

E

Economic competitiveness, 288–289

Economic figures, 197*f*

- infrastructure costs, 188, 196–198
- storage system costs, 188, 196

Economic target

- target costs, 285–286, 286*f*
- target prices
 - assumptions, 282–283, 283*t*
 - back-up of photovoltaic system, 284, 284*f*
 - carbon prices, 282
 - car fuel consumption, 283
 - hybrid system, 284, 285*f*
 - hydrogen market segments, 282–283, 283*t*
 - legal framework, 284–285
 - levelized cost of electricity, 284, 285*f*
 - set of batteries, 284, 284*f*

 ϵ -constraint method, 362, 376, 378Electricity generation, 4–5, 4*f*

Electric system services

- central production, 288–289, 289*f*
- characteristics of hydrogen production, 287
- local production, 287–288, 287–288*f*
- supply and demand, 286–287

Eley Rideal (ER) model, 139, 144–147, 145–146*t*

Elimination and choice translating reality (ELECTRE) method, 364

Energy Control Commission, 301–303

Energy demand, 4

Energy supply scenarios, PtG

- PtG-to-Power options, 336
- PtX applications, 335–336
- PtX capacities, 334*f*, 336, 337*t*
- REN electricity generation, 335–338
- REN integration, 334–335
- seasonal storage option, 333–334

Energy technology perspective (ETP), 334

Environment, Planning and Housing Regional Agency, 299

Equilibrium model, 358

European energy system construction process, 294

FFCEVs. *See* Fuel cell electric vehicles (FCEVs)

Fischer-Tropsch process, 316, 333

Fixed-bed catalytic reactor, 427

Fossil fuel-based syngas production, 317

Fossil fuels, 42

- coal, 43

economic and technical issues, 5
 global GHG emissions, 5
 natural gas, 43
 French Association for Hydrogen and Fuel Cells, 25
 Fuel Cell and Hydrogen Joint Undertaking (FCH JU), 334–335
 Fuel cell electric vehicles (FCEVs), 13, 168
 carbon emissions, 11–12
 CO₂ emissions, 11–12, 13*f*
 fuel cells, 14–16, 16*f*
 green/clean hydrogen, 11–12
 in market, 14, 16*f*
 market evolution in France, 14, 15*f*
 road transport alternatives, 14
 Fuel cell vehicles, 82–84
 Functional modeling
 GIS, 533–536
 hazard identification, 531–533
 HSC, 530–531, 531*f*, 532*t*
 QRA, 530
 socio-technical system, 529–530
 sustainability assessment
 comprehensive decision support, 536
 LCA/LCC assessment, 536, 537*f*, 538*t*
 Fuzzy systems, 358

G

Game theory, 358
 Gasoline vehicle (GV), 503
 Gauss-Jordan method, 355
 Genetic algorithms (GA), 378
 Geographic Information System (GIS), 380–381
 functional modeling, 533–536
 GHG emissions. *See* Greenhouse gas (GHG) emissions
 Gibbs free energy minimization method, 113
 Global warming potential (GWP), 69
 GraphML, 467–468
 Green gas applications
 global-warming potential vs. carbon dioxide, 275, 275*t*
 green gas pathways, 273, 275*f*
 greenhouse gas emissions, 275
 natural gas, 273
 power-to-gas, 273–275
 Greenhouse gas (GHG) emissions, 69, 275, 374–375
 average emissions, 104, 105*f*
 climate change, 5
 cumulative WtW life cycle, 70

fossil fuels, 5
 fuel cell vehicles, 82
 historic trends, 81, 82*f*
 HSC
 biomethane, 98–100
 German electricity mix, 98
 hydrogen supply pathways, 98, 99*f*
 hydrogen transportation options, 100–102, 101*f*, 103*f*
 from natural gas, 100
 pipeline transport, 102, 103*f*
 production steps contribution, 100, 101*f*
 thermochemical gasification, 98–100
 transport emissions, 99*f*, 100–102
 low-carbon and low-emission mobility, 81
 mobility sector, 81
 Green hydrogen, 9, 11–12, 30–31, 82, 112

H

High-pressure buffer, 244
 High-pressure hydrogen pipeline networks (HP network), 406–407
 High-pressure storage
 advantage, 170, 172
 categories, 170–171
 CFRP-tanks, 170–171, 171*f*
 safety valves, 172
 shapes, 169
 Homogeneity production, 299–301
 HRS. *See* Hydrogen refueling station (HRS); Hydrogen retail station (HRS)
 HSC. *See* Hydrogen supply chain (HSC)
 Hybrid vehicle (HV), 503
 Hydrocracking process, 423
 catalytic cracking, 424–425
 feedstocks, 424–425
 hydrogenation, 424–426
 hydrotreating process, 425
 inlet flowrate and hydrogen purity, 426
 low-pressure purge, 425–426
 process diagram, 425–426, 425*f*
 reactor, 425–426
 Hydrogen applications
 chemical product and an energy carrier
 “green” gas applications, 273–275, 275*f*
 hydrogen production, 271, 272*f*
 industry applications, 271–273
 mobility applications, 275–277
 stationary applications, 277
 hydrogen demand, 277–278
 hydrogen markets
 economic target, 282–286

- Hydrogen applications (*Continued*)
 - green gas, 280–281, 281*t*
 - for industry, 279
 - mobility, 281–282
 - stationary, 282
 - hydrogen systems
 - hydrogen to foster synergies, 289–290, 290*f*
 - services for electric system, 286–289
- Hydrogenation, 424–426
- Hydrogen compression, 208–209, 208*f*
 - cooled compression, 242–244
 - on distribution site, 239, 240*t*
 - economic data
 - compressor investment cost, 217–219, 218*f*
 - cost of pressure vessels, 219–220
 - technical data
 - compression efficiency, 214–216
 - compressor cooling, 216–217
 - isothermal/adiabatic compression work, 213–214
 - thermodynamic data, 211–212
- Hydrogen corridors, 26–30
- Hydrogen distribution
 - compression and storage (*see* Hydrogen compression)
 - distant refueling station supply (*see* Hydrogen transportation)
 - learning curve, 258
 - peak hour demand and buffer capacity, 229–231
 - refueling
 - buffer storage, 210, 210*f*
 - filling equipment, 209, 210*f*
 - HRS, 209–210
 - regulation valve controls, 209
 - storage buffer cost, 233–234, 234*t*
 - technical details and costs, 242, 246–247*t*
 - transportable storage containers, 244
 - transportation material, 245
- Hydrogen economy, 521, 524, 528–529
- Hydrogen energy carriers
 - liquid hydrogen (LH), 507–509, 508*f*
 - methylcyclohexane (MCH)
 - dehydrogenation, 511
 - domestic MCH/TOL distribution, tanker truck, 509
 - ocean transport, tanker, 509
 - production, 509
 - renewable hydrogen supply chain, 509–511, 510*f*
 - storage, discharging port, 509
 - storage, loading port, 509
 - TOL replacement, 511
 - TOL storage, discharging port, 511
 - TOL storage, loading port, 511
- Hydrogen, energy transition
 - advantages, 5
 - decarbonization, economy key sectors, 6–8, 6*f*
 - HSC (*see* Hydrogen supply chain (HSC))
 - near zero-emission energy carrier, 5
- Hydrogen Mobility Europe 2 (H2ME 2), 23
- Hydrogen pipeline model
 - compression factor, 411
 - hydrogen source, 411
 - mass balance equation, 410–411
 - numerical mass balance equation, 410–411
 - Peng-Robinson equation, 411
- Hydrogen production
 - biogas/landfill gas
 - characteristics, 112–113, 113*t*
 - green hydrogen, 112
 - reforming processes, 112–113
 - via syngas route, 112, 112*s*
 - biomass-based H₂ production, 85
 - categories, 47
 - CCS (*see* Carbon capture and storage (CCS))
 - centralization vs. decentralization level, 47–48
 - centralized production units, 529
 - conversion efficiencies, 85, 86*t*
 - decentralized, 529
 - electrolysis, 86–87, 93
 - alkaline electrolyzers, 51
 - operation principles, 49, 50*f*
 - PEM electrolyzer, 49–51
 - solid oxide electrolyzers, 51–54, 52*f*, 53*t*
 - feedstock, 85
 - fossil fuels, 42
 - coal, 43
 - natural gas, 43
 - gasification
 - biomass, 55–56, 55*f*, 93
 - coal, 54, 54*f*, 85
 - infrastructure, 83
 - fuel cell vehicles, 83–84
 - hybrid electric vehicles, 83
 - methane reforming (*see* Methane reforming)
 - method advantages and disadvantages, 57, 58*t*
 - power-to-hydrogen, 41–42
 - PtG concept

- alkaline water electrolysis, 311
- depressurization, 312
- electrolyzer shut down, 312
- natural gas grid, hydrogen blending to, 317–319, 318*f*
- PEM electrolysis, 311
- SOEC, 311–312
- refueling station, 85
- RES (*see* Renewable energy sources (RES))
- risks, 529
- SMR, natural gas, 48–49, 48*f*, 85–86, 93
- solid biomass gasification, 87–88
- steam reforming (*see* Steam reforming)
- sustainable production method, 528–529
- syngas, 112
- uranium and nuclear, 47
- water electrolysis, 112
- water-gas-shift-reaction, 85
- WGS, 112–113
- world net electricity generation, energy source, 42, 42*f*
- Hydrogen refueling station (HRS), 23
 - bulk storage, 210
 - investment cost, 209
 - parameters, 67, 68*t*
 - performance metrics, 209–210
- Hydrogen safety, 16–18, 17*t*, 19*f*
- Hydrogen society, 24
- Hydrogen storage, mobile application
 - GHG reduction, 167–168
 - material-based storage (*see* Material-based hydrogen storage)
 - options, 168, 169*f*
 - secondary energy carrier, 168
- Hydrogen supply chain (HSC)
 - biomass gasification, 90
 - complex infrastructure, 527
 - decision levels, 351
 - deployment strategies
 - economic barriers, 18–21, 20*f*
 - hydrogen technologies and improvements, 18, 19*f*
 - infrastructure development and roadmaps (*see* Infrastructure development and roadmaps)
 - roadmaps and transition plan scenarios, 26–31, 30–31*f*
 - social acceptance and safety barriers, 21–22
- design
 - deterministic optimization approaches, 372–375
 - GIS, 380–381
 - hydrogen-based energy system taxonomy, 366, 367–371*t*
 - multiobjective optimization and MCDM, 375–378, 377*f*
 - multi-period nature, 378–379
 - potential HSC pathways and specifics, 372
 - sensitivity analysis, 380
 - supply chain uncertainty, 379–380
- dynamic simulation
 - applied architecture, 489
 - electrical energy generated, photovoltaic process, 490, 490*f*
 - photovoltaic-generated energy, 490, 490*f*
 - wind power energy generation, 490–491, 491*f*
- electrolysis
 - based on electrical energy from wind power, 90
 - based on electricity from solar radiation, 90
 - based on grid power, 90
- energy demand, 96–98, 97*f*
- and energy requirements
 - CO₂ emissions, 207–208
 - distribution (*see* Hydrogen distribution)
 - energy loss, 207–208
 - hydrogen compression, 208–209, 208*f*
 - large-scale production, 207
 - overall energy chain, 207
 - transportation, 207–208
- environmental and energy benefit
 - BEV, 13–14
 - CO₂ emissions, 11–13, 13*f*
 - decarbonization, 13–14
 - FCEVs (*see* Fuel cell electric vehicles (FCEVs))
 - GHG emissions, Europe and France, 11–12, 12*f*
 - hydrogen safety, 16–18, 17*t*, 19*f*
 - PHEV, 13–14
- feedstock and energy resources
 - electricity, 91, 92*t*
 - hydrogen production, 93
 - methane, 91, 92*t*
 - solid biofuels, 92, 93*t*
- feedstock for industrial uses
 - coal gasification, 41
 - SMR, 41
 - syngas process, 41
 - worldwide hydrogen consumption, 39, 40*t*

Hydrogen supply chain (HSC) (*Continued*)gasoline, 512–513, 513*f*

GHG emissions, 501

average emissions, 104, 105*f*

biomethane, 98–100

German electricity mix, 98

hydrogen supply pathways, 98, 99*f*hydrogen transportation options, 100–102, 101*f*, 103*f*

from natural gas, 100

pipeline transport, 102, 103*f*production steps contribution, 100, 101*f*

thermochemical gasification, 98–100

transport emissions, 99*f*, 100–102

green hydrogen, 82

HRS (*see* Hydrogen refueling station (HRS))

hydrogen conditioning and storage, 60

gaseous hydrogen (GH₂), 60–61liquid hydrogen (LH₂), 61

solid hydrogen, 61–62

storage parameters, 62, 63*t*storage pathways, 60, 60*f*

hydrogen energy carriers, 507–511

hydrogen fueling, FCVs, 512

hydrogen produced by NG reforming

compressed hydrogen (CH) production, 512

domestic CH distribution, tanker truck, 512

steam reforming, 511

hydrogen production (*see* Hydrogen production)hydrogen transportation (*see* Hydrogen transportation)

LCA, 89, 500–501

MILP, 392–393

modeling, 461–462

multiobjective optimization

(*see* Multiobjective life cycle optimization)

multiple echelons, 38

multiple objectives, 38

multiple periods, 38

multiple stakeholders, 38

multiple users, 38

multiscale and multiobjective problem, 350

overview, 503–506

process modeling, design and operation, 464–465

programmable structures

applications, 468

declaration, metaprototypes, 474–477

direct computer mapping, 466–467

dynamic model-based (sub) optimization, 491

generation, GraphML file, 483

Prolog syntax, 477–480

state and transition elements, 492–494

GraphML text, 487–488

PtG concept (*see* Power-to-Gas (PtG) concept)

renewable hydrogen production, water electrolysis, 506–507

renewable power generation, 506, 506*t*risk analysis (*see* Risk assessment and management)SCM and design literature (*see* Supply chain management (SCM))

simulation-based problem solving, 487–488

SMR

from biogas, 90

from natural gas, 89

sustainable assessment

economic assessment, 67–68

environmental assessment, 69–70

social assessment, 70–71

sustainable development, 67

total daily social cost minimization, 527

transportation

distribution, 62

hydrogen pipelines, 64, 64*f*hydrogen tube trailers, 64, 64*f*parameters, 65, 66*t*

tanker trucks, 65

transmission, 62

TtW energy performance, 513, 513*t*, 514*f*

well-to-tank, 83

WtT GHG emissions

for hydrogen carriers, 514–516

target vehicles, 516–517, 517*f*variation in hydrogen, 516, 517*f*Hydrogen supply lines (HSL), 439, 442*f*, 452–454

Hydrogen technologies

Myrte platform, 293–294

smart grids, 293–294

socio-technical network, 299–301

Hydrogen Territory initiative, 25–26

Hydrogen transportation, 207–208

compressed hydrogen, 88

compression

on distribution site, 239, 240*t*on production site, 237–239, 238*t*

electricity transport, 95

- energy costs, 235
 - energy demand, compression/vaporization
 - at refueling station, 96, 96*t*
 - liquid transportation, 88–89
 - pipelines, 88, 94, 94*t*
 - trucks, 88
 - compressed, 94, 94*t*
 - liquefied, 95
 - Hydrogen vehicles vs. electric vehicles, 111
 - Hydropower, 46
 - Hydrotreating process, 423, 425
 - HyFrance3 project, 25
 - HYRREG project, 24
 - HyWays project, 23
- I**
- Infrastructure development and roadmaps
 - California, 25
 - European level, 23–24
 - France, 25–26
 - Germany, 24
 - Iceland, 24
 - Japan, 24
 - United States, 24–25
 - worldwide level, 23
 - Internal combustion engine (ICE) vehicle, 11–13, 13*f*
 - Inventory Database for Environmental Analysis (IDEA), 505
 - Isentropic compression, 213–215
 - Isothermal compression, 213
- L**
- Langmuir Hinshelwood-Hougen Watson (LHHW) model, 139, 144–147, 145–146*t*
 - LCA. *See* Life cycle assessment (LCA)
 - LCC. *See* Life cycle costing (LCC)
 - Lexicographic method, 360, 376
 - Life cycle assessment (LCA), 69, 89, 375, 500–501
 - Light hydrocarbon recovery, 428
 - Limiting composite curve (LCC), 439, 442*f*, 452–454
 - Linear formulation
 - LP models, 354–355
 - methods, 354
 - MILP, 354–355
 - Linear programming (LP) models, 354–355
 - Liquefied natural gas (LNG), 503–505
 - Liquid hydrogen (LH), 514–515, 514*t*, 515*f*
 - Liquid transportation, 88–89
 - LOHC. *See* Liquid organic hydrogen carrier (LOHC)
 - Low-pressure hydrogen pipeline networks (LP network), 406–407, 409
- M**
- Market aspects, 198, 199*f*
 - compatibility with existing infrastructure, 191, 201
 - market proximity 2025/30, 191, 200–201
 - market proximity today, 191, 199–200
 - Markov chains, 358
 - Markov decision process (MDP), 357
 - Material-based hydrogen storage
 - activated carbon, 185–187
 - LOHC (*see* Liquid organic hydrogen carrier (LOHC))
 - metal hydride storage
 - advantages, 180
 - covalent hydrides, 179
 - gravimetric energy density, 180
 - hydrogen adsorption, 178, 178*f*
 - ionic/saline hydrides, 179
 - light-weight metal hydride, 177–178
 - markets and perspectives, 180–181
 - metal hydrides, 179
 - principle, 178–179
 - thermal management, 180
 - TiFe, 177–178
 - MOF, 183–185
 - reversible physical effects, 177
 - single-storage option, 177
 - Mathematical Programming with Equilibrium Constrained (MPEC) method
 - two-level programming problems, 416
 - Mean-time-to failure (MTTF) parameters, 544–545, 545*t*
 - Mean time to repair (MTTR) parameters, 544–545, 545*t*
 - Membrane process, 428
 - Metaheuristic methods, 362
 - Metal hydride storage
 - advantages, 180
 - covalent hydrides, 179
 - gravimetric energy density, 180
 - hydrogen adsorption, 178, 178*f*
 - ionic/saline hydrides, 179
 - light-weight metal hydride, 177–178
 - markets and perspectives, 180–181
 - metal hydrides, 179
 - principle, 178–179

- Metal hydride storage (*Continued*)
 - thermal management, 180
 - TiFe, 177–178
- Metal organic framework (MOF)
 - characterization and status, 184–185
 - markets and perspectives, 185
 - MOF-5 structure, 184, 184f
 - organic ligands, 183
 - principle, 184
- Methane production, PtG concept
 - biologic methanation, 315–316
 - carbon dioxide separation, 313
 - catalytic methanation, 313–314
 - Sabatier reaction, 313
- Methane reforming
 - chemical reactions, 113, 114t
 - dry reforming (*see* Dry reforming of methane (DRM))
 - FactSage calculation, 113
 - Gibbs free energy minimization method, 113
 - with mixture of steam/carbon dioxide (*see* Dual methane reforming (DMR))
 - with steam (*see* Steam methane reforming (SMR))
 - TRM (*see* Tri-reforming of methane (TRM))
- Methane repowering, 9
- Methylcyclohexane (MCH)
 - dehydrogenation, 511
 - domestic MCH/TOL distribution, tanker truck, 509
 - ocean transport, tanker, 509
 - production, 509
 - renewable hydrogen supply chain, 509–511, 510f
 - storage, discharging port, 509
 - storage, loading port, 509
 - TOL replacement, 511
 - TOL storage, discharging port, 511
 - TOL storage, loading port, 511
- MILP. *See* Mixed-integer linear programming (MILP)
- Ministry of Economy, Trade, and Industry (METI), 24
- Mixed-integer linear programming (MILP), 354–355, 392–393, 405
 - capacity constraints, 395–396
 - mass balance, 395
 - objective function calculations
 - environmental impact, 398–400, 399f
 - total cost (TC), 397–398
- Mixed integer nonlinear programming (MINLP), 356
- Mobility applications
 - aeronautics companies, 275–276
 - environmental footprint, 276–277
 - hydrogen bicycle, 275–276, 276f
 - hydrogen car, Toyota Mirai, 276, 277f
 - hydrogen range-extender car, 276
 - market maturity, 276
 - passenger vehicles, 276
- Model for Optimization of Regional Hydrogen Supply (MOREHyS) approach, 380
- Model generation, 473–474, 488
- Modeling framework, 405
- Modified TOPSIS (M-TOPSIS) method, 365
- MOF. *See* Metal organic framework (MOF)
- Momentum balance equation
 - average pressure calculation equation, 412
 - average pressure of pipeline, 412
 - collocation method, 412
 - flow pattern, Reynolds number, 415
 - hydrogen storage capacity, 414
 - momentum conservation equation, 412
- Monoobjective optimization, 360, 375
- Multiobjective life cycle optimization
 - mathematical formulation
 - MILP model (*see* Mixed-integer linear programming (MILP))
 - problem statement, 394, 394f
 - solution procedure, 400
 - numerical results, Pareto solutions, 401, 401f
- Multiobjective optimization
 - a posteriori preference methods
 - ϵ -constraint method, 362
 - metaheuristic methods, 362
 - a priori preference methods
 - aggregative methods, 359–361
 - lexicographic method, 360
 - weighted sum, 360
 - hybrid methods, 363
- MCDM
 - bi-criterion formulation, 375
 - DEMATEL method, 376–378
 - environmental impact, 375
 - ϵ -constraint method, 376, 378
 - fuzzy linear programming, 378
 - genetic algorithms, 378
 - lexicographic method, 376
 - mixed integer linear programming, 376
 - M-TOPSIS analysis, 376
 - NPV, 375–376
 - objective functions, 378
 - weighted sum, 378
- Pareto front, 359

Multiperiod optimization model, 527
 Multiple criteria decision-making (MCDM)
 approaches, 363–365

N

National Innovation Program for Hydrogen and
 Fuel Cell Technology NIP (2006–16),
 24
 Natural gas grid, hydrogen blending to,
 317–319, 318*f*
 Negative Ideal Solution (NIS), 364–365
 Net Present Value (NPV), 375–376
 Neural networks, 358
 Nonlinear formulation, 356
 Nuclear flexibility, 289

O

Office Parlementaire d’Evaluation des Choix
 Scientifiques et Technologiques
 (OPECTS), 25
 Operational planning, 351
 Overseas chain, 503–505
 Oxidative DRM, 147

P

Pareto front, 359
 Paris Agreement, 167
 Paris Climate Agreement, 4
 Passenger transport volumes, 81
 PEM. *See* Polymer electrolyte membrane
 (PEM)
 Pinch technique, hydrogen network, 423–424
 hydrogen network design, 439, 442*f*
 Plug-in hybrid electric vehicles (PHEV),
 13–14
 Polymer electrolyte membrane (PEM)
 electrolysis, PtG, 311
 electrolyzer
 anode reaction, 49–51
 cathode reaction, 49–51
 operation principles, 50*f*
 Positive Ideal Solution (PIS), 364–365
 Power law model, 139–144, 143*t*, 147
 Power-to-Gas (PtG) concept
 biological methanation, 10–11
 green hydrogen, 9
 hydrogen production
 alkaline water electrolysis, 311
 depressurization, 312
 natural gas grid, hydrogen blending to,
 317–319, 318*f*

 PEM electrolysis, 311
 SOEC, 311–312
 methane production
 biologic methanation, 315–316
 carbon dioxide separation, 313
 catalytic methanation, 313–314
 Sabatier reaction, 313
 pathways and components, 309, 310*f*
 process chain, 9–10, 10*t*
 PtG projects, 319, 320–330*t*
 PtH, 9
 spatial distribution, 319–331, 331*f*
 supply chains, 8–9, 8*f*
 synthesis gas production, 316–317
 synthetic methane production, 9
 technical and economic barriers, 10–11
 thermochemical methanation, 10–11
 Power-to-Hydrogen (PtH)
 concept, 9
 projects, 319
 Pressure swing adsorption (PSA)
 carbon dioxide and impurities removal,
 427
 feed flow rate, 451–452, 455*f*
 feed hydrogen purity, 451–452
 purification unit, 451, 454*f*
 Pressure swing adsorption process, 428
 Process hydrogen sources, 443
 Programmable structures
 direct computer mapping, 466–467
 Prolog syntax, 477–480
 spatial coordinates, 480
 uncertainty, model parameters, 492
 Prolog kernel program, 467–468
 PSA. *See* Pressure swing adsorption (PSA)
 PtG concept. *See* Power-to-Gas (PtG) concept
 PtG-to-Chemicals projects, 319
 PtG-to-Power options, 336
 PtG-to-Transport option, 336
 PtH. *See* Power-to-Hydrogen (PtH)
 Pure hydrogen
 cryo-compressed hydrogen
 characterization, 176
 markets and perspectives, 176–177
 high-pressure storage
 advantage, 170, 172
 categories, 170–171
 CFRP-tanks, 170–171, 171*f*
 characterization, 172
 safety valves, 172
 liquid hydrogen storage
 markets and perspectives, 175

Pure hydrogen (*Continued*)

- tank shapes, 173
- techno-economic constraints, 173
- volumetric storage density, 173

Q

Quantitative risk assessment (QRA), 530, 539

Queuing models, 358

R

Re-electrification, 277

Refinery hydrogen system

- hydrocracking, hydrogen consumers
 - catalytic cracking, 424–425
 - feedstocks, 424–425
 - hydrogenation, 424–426
 - hydrotreating process, 425
 - inlet flowrate and hydrogen purity, 426
 - low-pressure purge, 425–426
 - process diagram, 425–426, 425f
 - reactor, 425–426
- hydrogen producers, 426–427, 427f
- industrial hydrogen purification process, 427–428
- insight-based pinch technique (*see* Pinch technique, hydrogen network)
- mathematical programming approach (*see* Superstructure-based mathematical programming approach)
- purification unit, 451, 454f
- recycle hydrogen streams, 449–451
- total number of connections, 451–452, 455f

Refueling

- with a compressor and a buffer, 267–268, 268f
- energy costs, 221–222, 221–222t
- principles
 - buffer storage, 210, 210f
 - filling equipment, 209, 210f
 - HRS, 209–210
 - regulation valve controls, 209
- with several storage units, 264–267, 266f

Regional Direction of Industry, Research and Environment, 299

Renewable energy sources (RES), 42

- biomass, 44–45
- hydropower, 46
- solar energy, 45
- wind, 45–46

RES. *See* Renewable energy sources (RES)

Reverse water gas-shift reaction, 158–159

Risk assessment and management

- consequence modeling, 523
- dynamic risk analysis
 - DES model logic, 540–543, 541f
 - QRA, 539
- energy process control, 522
- functional modeling (*see* Functional modeling)
- Haimes' 10 guiding principles, 523, 525–526t
- hydrogen economy, 521, 524, 528–529
- hydrogen production
 - centralized production units, 529
 - decentralized, 529
 - sustainable production method, 528–529
- meta-models, 527
- performance-based fire safety engineering approach, 522–523
- prenormative safety risk research, 523
- safety risk modeling
 - MTTF and MTTR parameters, 544–545, 545t
 - SimEvents commercial software package, DES, 543

Robust engineering strategy

- data reconciliation method, 405
- flowchart of HP network system, 407, 408f, 409
- hydrogen purification network, 405–406
- instability problems, 417
- load decision of compressors, 420, 420f
- MILP model, 405
- momentum balance equation, 412–415
- MPEC method, 409, 416–417
- nonlinear planning model, 405
- operational optimization, 418f, 419–420
- real-time data, 417–418
- refinery process, schematic representation, 406–407, 407f

S

SBR. *See* Steam biogas reforming (SBR)

SCM. *See* Supply chain management (SCM)

Segmentation function, 409–410

SMR. *See* Steam methane reforming (SMR)

SOEs. *See* Solid oxide electrolyzers (SOEs)

Solar energy, 45

Solid biofuels, 92, 93t

Solid oxide electrolyzer cell (SOEC), 311–312, 332–333

Solid oxide electrolyzers (SOEs)

CAPEX, 53

- electrolysis flow diagram, 51, 52*f*
 - operation principles, 50*f*
 - solid ceramic material, 51
 - solid oxide fuel cell (SOFC), 51
 - specifications, 53, 53*t*
 - Solid polymeric membrane (SPE)
 - electrolyzer, 331
 - Steam biogas reforming (SBR)
 - biogas cleaning, 124
 - biogas compression, 124
 - biogas feeding, 123, 124*t*
 - biogas heating, 125
 - biogas production plants capacity, 123
 - block diagram, 124–127, 125*f*
 - CO₂ separation, 123–124
 - direct SBR, 123–124
 - energy balance, SBR+WGS reactors, 128, 128*t*
 - energy efficiency, 127, 127*t*
 - gas composition, 125, 126*t*
 - heat production, 127
 - H₂ separation, 125
 - pure hydrogen compression and storage, 125
 - reformate mixture cooling, 125
 - small-capacity unit, 128
 - vs. SMR, 123
 - VABHYOGAZ project, 123–124, 125*f*
 - WGS catalytic reactor, 125
 - Steam methane reforming (SMR), 11–12, 463–464
 - alumina-supported nickel catalysts, 121–122
 - from biogas, 90
 - block diagram, 427, 427*f*
 - kinetic models, 128–132
 - from natural gas, 89
 - nickel-based catalysts, 121–122
 - performance figures, 121, 122*t*
 - process
 - H₂ separation, 121
 - natural gas pretreatment, 120
 - steam generation, 120
 - steam reforming, 114*t*, 121
 - WGS, 121
 - vs. SBR, 123
 - thermodynamic equilibrium
 - atmospheric pressure, 117
 - chemical reactions, 114–115, 114*t*
 - CH₄-H₂O mixture, 114–115, 115*f*
 - equimolar ratio of H₂O/CH₄, 115
 - molar ratio of H₂O/CH₄, 115–117, 116*f*
 - reaction pressure, 117–118, 117*f*
 - Steam reforming, 112, 112*s*
 - methane reforming
 - with mixture of steam/carbon dioxide (see Dual methane reforming (DMR))
 - with steam (see Steam methane reforming (SMR))
 - SBR process (see Steam biogas reforming (SBR))
 - Stochastic programming, 356
 - Storage containers
 - emptying, higher-pressure buffer, 260–263, 262–263*t*
 - progressive filling, 258–260, 260*t*
 - transportable, 244
 - Strategic planning, 351
 - Superstructure-based mathematical
 - programming approach, 423–424
 - mathematical formulations
 - connection and pressure constraints, 447–448
 - fuel system, 447
 - problem statement, 443
 - Supply chain management (SCM), 38
 - dynamic programming, 356–357
 - equilibrium model, 358
 - linear formulation, 354–355
 - mathematical programming, 353–354
 - MCDM approaches, 363–365
 - multiobjective formulation (see Multiobjective optimization)
 - nonlinear formulation, 356
 - optimization methods, 351–353, 352–353*t*, 354*f*
 - single-objective optimization problem, 354
 - supply chain network design under uncertainty, 365–366, 366*t*
 - Supply chain network design (SCND), 365–366, 366*t*, 462
 - Synthesis gas production, 316–317
 - Synthetic natural gas (SNG), 313–314
- ## T
- Tactical planning, 351
 - Tank-to-wheel (TtW), 503
 - Technical values
 - capacities, hydrogen storage technologies, 192, 192*f*
 - gravimetric energy density, 188, 192–194
 - idle storage conditions, 192, 194*f*
 - overall energy density, 188, 195
 - storage conditions at idle state, 188, 194*f*, 195–196

Technical values (*Continued*)

- system fill rate, 188, 192, 193*f*, 195
- volumetric energy density, 188, 194
- WtFC efficiency, 188, 195

Technique for Order Preference by Similarly to Ideal Solution (TOPSIS), 364–365

Testudo hermanni, 299–301

Thermochemical methanation, 10–11

Thermodynamic equilibrium

- DMR, 118–119, 119–120*f*

DRM

- equimolar mixture, CH₄ and CO₂, 133, 133*f*
- molar mixture, CO₂/CH₄, 133–134, 133*f*
- reaction pressure, 134, 134*f*

SMR

- atmospheric pressure, 117
- chemical reactions, 114–115, 114*t*
- CH₄-H₂O mixture, 114–115, 115*f*
- equimolar ratio of H₂O/CH₄, 115
- molar ratio of H₂O/CH₄, 115–117, 116*f*
- reaction pressure, 117–118, 117*f*

TRM, 148–149, 148*f*

Time-on-stream (TOS), 134–135

Total annualized cost (TAC), 449

Total primary energy supply (TPES), 4–5, 4*f*

Transportable storage containers, 244

Transportation material, 245

Treaty of Lisbon, 294

Tri-reforming of methane (TRM)

catalysts

- endothermic steam reforming, 149
- exothermic partial oxidation, 149
- extent of interaction, 160
- Ni-based catalysts, 149
- promoters, 152–153, 154–156*t*

supports, 149–151

synergetic effect, 160

kinetic model

- activation energies and reaction orders, 153–158, 157*t*

Boudouard reaction, 158–159

- four-step reaction mechanism, 158–159, 158*t*

- kinetic expressions and associated parameters, 159, 160*t*

mechanistic reaction pathways, 153

Ni catalysts, 153

reaction order for CO₂, 153–158, 158*t*

reaction rate, 153–158

reverse water gas-shift reaction, 158–159

- thermodynamic equilibrium, 148–149, 148*f*

TRM. *See* Tri-reforming of methane (TRM)

U

Uncontrolled flow of energy (UFOE) model, 522

US Department of Energy (DOE), 24–25

V

Very-high-pressure buffer (VHPB), 232

W

Water-gas-shift (WGS) reaction, 112–113

Weighted sum method, 360, 378

Well-to-tank (WtT), 503

Well-to-wheel (WtW) life cycle, 70

Well-to-wheel (WtW) studies, 500–501

Wind, 45–46

World fuel shares, 4–5, 4*f*World total final consumption by fuel, 4–5, 4*f*